



COLO 7000

Vinyl matt paint for quality work
EXTERIOR/INTERIOR



DESCRIPTION

Matt paint based on an acrylic co-polymer.

FIELD OF USE

Colo 7000 can be applied on interior, exterior masonry, wood and plaster. It has a high degree of whiteness, an excellent covering power and a good adhesion. It dries quickly, has no smell and does not chalk.

TECHNICAL CHARACTERISTICS

- Aspect : Matt
- Colors : White, can be tinted with Teintes 2000 colorants. Special colors are supplied for above 100 Kg commands
- Spreading-rate : 5 to 6 m²/Kg per coat depending upon the support porosity .
- Density : 1.63-1.73 Kg/L ± 0.05 to 25°C.
- % Solids (by weight) : 74% ± 2%.
- Viscosity : 480-550 Poises at 25°C with the BrookField at 25°C

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- *Sand with a sandpaper.
- *Remove the dust.
- *Sand vigorously with Chiendent brush.
- *Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Colo 7000 can be applied with a brush or a roller without any risk of wet-edge problems.
Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USGE

- Dilution:
- * 1st coat 15 to 20% with water
 - * 2nd coat 10% to 15% with water

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.
Edition : June 2016 by Colorado (06/16).
This version cancel and replace the previous.

DRYING TIME

Drying at 20°C and 60% of humidity
* Touch Dry : 15 mn
* Through Dry : 30 mn.

RECOMMENDED SYSTEM

EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20	1
COLOPRIM	1
COLO 7000	2

INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B805 or SP88	2
COLO 7000	2

STORAGE

Six month in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before use.

PACKAGING

1 kg, 5 kg, 10 kg, 30 kg and 50 kg.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.
Fore more details, consult the safety data sheet N° 70.