



STUCCO Ksour

Water-based decorative render giving a marble like finish
INTERIOR/EXTERIOR



DESCRIPTION

Ksour is a water-based decorative render based upon an acrylic emulsion.
Contains a fungicide.

FIELD OF USE

It is designed for exterior decoration (due to its anti-fungal properties), giving a marble like, traditional finish. It has a high degree of whiteness and excellent scrub resistance.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty render.
- Colors : Blanc, teintes : see our catalogue.
- Spreading-rate : 3 to 4 m² / kg (2 Coats).
- Density : 1.54 +/- 0.05 Kg/L to 25°C.
- Viscosité : 1000 poises +/- 200 to 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Using a roller, apply an even coat of Ksour over the surface.

Before the product dries, spread out the Ksour in all directions using a triangular plastic rendering tool. To reduce the risk of lapping problems, work in areas of 1 to 2m².

Leave the product for approximately seven hours to dry. Using a blade or rendering tool, scratch the surface to remove any uneven product.

Apply a second coat of Ksour, without dilution. Ksour should be applied with a suitable trowel.

Wait for three or four hours and then with the special trowel, accentuate the differences in colour to achieve the marble-like effect.

If the trowel is not plastic, it's necessary to protect the blade with a cloth, before using. The use of a steel trowel will leave grey marks on the surface of Ksour. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

Edition : June 2014 by Colorado (DC 28 D).
This version replaces all previous editions.

APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Can be diluted with water.

DRYING TIME

- *1st coat : 12h
- *2nd coat : 4h

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505	2
COLOVINYL 600	1
STUCCO RIYAD	2

■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20	1
COLOPRIM	1
COLOVINYL 600	1
STUCCO RIYAD	2

STORAGE

One year in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

5 kg, 10kg and 25kg

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.
Fore more details, consult the safety data sheet N° 21.