



IMPREX

Impregnation varnish based on modified
synthetic binders

DESCRIPTION

Imprex is designed to water-proof masonry surfaces. It is a new generation of selective waterproofing by combining water resistance with water vapour permeability.

FIELD OF USE

Recommended for application on exterior and interior masonry walls.

TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Color : Transparent.
- Spreading-rate : 14 to 16 m² after dilution with 100 % of white spirit.
- Density : 0.90 +/- 0.05 Kg/L at 25°C.
- % Solids (by weight) : 30 +/- 2%.
- Viscosity : 45 seconds +/- 10 with the Ford Cup Number 6 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering. Eliminate the causes of the humidity before starting to remedy its effects.

APPLICATION PROPERTIES

Is applied by roller or brush.
Limitation of use: Do not apply on condensing or frozen support at temperatures below 7 °C, nor relative humidity above 70%.

APPLICATION DETAILS FOR USAGE

Dilution : D66 (WHITE SPIRIT).

DRYING TIME

Drying at 20°C and 60% relative humidity :

*Touch dry	: 20 min
*Dry	: 1h30
*Recoverable	: after 3h

STORAGE

One year in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures., however it is recommended to stir the product before use.

PACKAGING

1.5 and 20 liters.

HEALTH & SAFETY

Flammable product and toxic to humans and the environment.
For more details, consult the safety data sheet N° .