



DESCRIPTION

Gloss emulsion paint based on acrylic resin and water.

FIELD OF USE

ACRYLAC is a water-based lacquer specially designed for new interior and exterior work such as bathrooms, kitchens and exhibition walls. ACRYLAC is distinguished by:

- * A very high opacifying and whiteness power.
- * Very high shine.
- * Very easy to apply.
- * Very high exterior durability (maximum resistance and permeability to water vapor).
- * Very low odor during application.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss and smooth.
- Colors : A choice. Special colors are delivered for orders over 100 kg.
- Spreading-rate : 14 to 16 m²/Litre depending on the porosity of the support.
- Density : 1,17 +/- 0,05 at 25°C.
- Viscosity : 105 +/- 5 KU at 25°C with the Krebs viscometer.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Substrate condition: Sound, dry and carefully prepared. Can be applied directly to concrete. If the substrate presents a high risk of support for microorganisms (algae, fungus) ask for the version with Fungicide. Preparation of the support: Grind, clean, brush and remove dust. Recommended material: Brush or roller. Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 °C and / or relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: water

DRYING TIME

Drying at 20 °C and 60% humidity:

- * Dust dry: 30 min.
- * Dry: 4 hours.
- * Recoatable after 24 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
SUPER PATENDUIT SP88	2
COLOSTOP	1
ACRYLAC	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

3L, 10L.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 95.

MINIMUM ORDER QUANTITY

Please contact our sales department .

Edition : August 2025 by Colorado 08/25 (DC28G).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001