

DESCRIPTION

Decorative paint specially designed to embellish interiors and provide a particularly cozy and sparkling atmosphere.

FIELD OF USE

Recommended for application on interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Slightly metallic and pearly with silver glitter.
- Color : According to our color chart.
- Spreading-rate: +/- 4m²/kg (in 2 coats), in accordance with ISO 23811 (2009).
- Density: 1,17 +/- 0,05 for the silver base 25 ° C, in accordance with standard NM ISO 2811-1 (2008).
- Viscosity: 1250 +/- 50 Poises at 25° C (Brookfield).

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Apply a coat of COLOFONDO and let dry for 12 hours. Apply the first coat of ALMAZ (diluted with water up to 20%) and let dry for 6 hours. Apply a second coat of ALMAZ and possibly a third coat (diluted up to 20% with water).

Immediately afterwards, smooth the surface using a plastic float with circular movements.

APPLICATION DETAILS OF USAGE

Dilution: Product ready to use. Mix the product well with a spatula before use. May be diluted up to 20% with water depending on application method used.





DRYING TIME

Drying at 20 ° C and 60% humidity:

- * Dust free: 1 to 2 hours.
- * Recoatable: 6 hours.
- *Washable after 20 days.

RECOMMENDED SYSTEM

■ INTERIOR (Consult us):

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOFONDO	1
ALMAZ	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

2,5 kg and 20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 321.

Edition: November 2023 by Colorado 11/23 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001