



DESCRIPTION

AMANLAC is an ecological paint in aqueous phase with a smooth glossy aspect, having a great resistance to washability and yellowing. AMANLAC has a very low odor upon application.

FIELD OF USE

Gloss paint for all interior and exterior wall surfaces.

TECHNICAL CHARACTERISTICS

- Aspect : Brillant and smooth.
- Colors: White, it can be tinted with our Tints 2000 (do not exceed 5%).
- Spreading rate : 10 to 12 m²/kg according to the porosity of the support.
- Density : 1,26 +/- 0,05 at 25°C.
- Viscosity : 115 +/- 5 KU at 25°C with the Krebs viscometer.

SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Condition of the surface: sound, dry and carefully prepared. Apply the 1st coat of AMANLAC diluted up to 10% with water.

Apply the 2nd coat diluted up to 5% water.

Recommended material: Brush or roller.

Limits of application: Do not apply to condensing or frozen supports, at temperatures below 5°C and/or relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: with water .

DRYING TIME

Drying at 20°C and 60% humidity:

- * Dust free: 30 min.
- * Dry : 4 hours.
- * Recouvrable after 12 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
SUPER PATENDUIT SP88	2
COLOSTOP	1
AMANLAC	2

STORAGE

The product can be stored for up to 2 years under good storage conditions, away from sunlight and frost, in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

4kg, 15kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°315.

Edition : February 2022 by Colorado 02/22 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001