



AQUAVERNIS

INTERIOR/EXTERIOR



DESCRIPTION

Water-base varnish based upon a pure acrylic resin.
Algaecide and fungicide Varnish.

FIELD OF USE

A water-based varnish, designed for the exterior protection of sensitive coatings and the interior protection of decorative effect paints.

TECHNICAL CHARACTERISTICS

- Aspect : Satin finish.
- Colors : Transparent.
- Spreading-rate : About 8 m²/L depending upon the porosity of the substrate, per coat.
- Density : 1.02 +/- 0,05 Kg/L @ 25° C.
- Viscosity : Ford Cup N°4 33 seconds +/- 2 @ 25°C.

SURFACE PREPARATION

Smooth, clean, dust-free surfaces should be prepared.

APPLICATION PROPERTIES

Do not apply on cold, wet walls below 5°C or in conditions of high relative humidity, greater than 70%.
Substrate conditions : Sound, dry and well prepared.
Application : Brush or roller.

APPLICATION DETAILS FOR USAGE

Ready to use

DRYING TIME

Drying time at 20°C and 60% relative humidity :
* Touch dry : 30 min
* Dry : 60 min
* Recoat able after a minimum 4 hours

RECOMMENDED SYSTEM (Consult us)

■ INTERIOR/EXTERIOR

SYSTEM	NUMBER OF COATS
DECORATIVE PAINTING	1
AQUAVERNIS	2

STORAGE

Two years in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

800 ml.

HEALTH & SAFETY

No special precautions are necessary. Water-based coating. Do not throw un-used paint into the public sewage system.
For more details, consult the safety data sheet N°247.

Edition : June 2019 by Colorado (06/19).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.