



## DESCRIPTION

Decorative coating in waterborne.

## FIELD OF USE

Specially designed for the embellishment of interiors and dresses your interior with a particularly cozy atmosphere.

## TECHNICAL CHARACTERISTICS

- Aspect : Pearly.
- Colors : According to our color chart, 103 colors available.
- Rendement : 7 to 8 m<sup>2</sup>/Kg.
- Density : 1,12 +/- 0,05 for the neutral base at 25° C.
- Viscosity : 108 +/- 5 KU at 25° C.

## CONDITIONS AND METHODS OF APPLICATION

Using a special brush, apply with alternating brush strokes ARABESK.  
10 minutes later, lightly smooth the painted surface using the spatula designed for this purpose.

## APPLICATION DETAILS OF USAGE

Ready to use product. Mix the product well with a spatula before use.  
The substrate is prepared with one or two coats of Colofondo paint and let dry for 12 hours.

## DRYING TIME

- Drying at 20 ° C and 60% humidity:
- \* Dust free: 3 to 4 hours
  - \* Dry: 24 hours
  - \*Washable: after 20 days (after applying a COLOPRIM topcoat).

## RECOMMENDED SYSTEM

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOSTOP	1
COLOFONDO	1
ARABESK	1

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

2,5 kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°27.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.  
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001