



DESCRIPTION

ARMONY is a water-based decorative paint with iridescent highlights.

FIELD OF USE

Recommended for application on interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Pearly
- Colors : According to our color chart.
- Spreading-rate : 4 to 5 m²/Kg (in 1 layers), in accordance with ISO 23811 (2009).
- Density : 1.30 ± 0.05 at 25° C, complies with NM ISO 2811-1 (2008).
- Viscosity : 1000 ± 100 poises (M6/10) at 25° C (Brookfield).

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

- 1- Apply a coat of COLOFONDO and allow to dry for 12 hours.
- 2- Apply a first coat of ARMONY using a decorative spatula, plastic float or stainless steel float, ensuring a perfectly smooth, even surface.
- Allow to dry for 4 hours.
- 3- Dilute ARMONY with up to 10% water, then create the desired decor using a plastic float or special deco trowel, creating patterns on surfaces of 1 to 2m² maximum.
- 4- After 5 to 10 minutes, smooth the surface with a plastic or stainless steel float to obtain a smooth, shiny finish.
- 5- For a brighter effect, gently rub the surface with a special sponge.

APPLICATION DETAILS OF USAGE

Dilution: ready to use. (Can be diluted up to 10% water).
Mix the product well with a spatula before use.

DRYING TIME

Drying at 25 ° C and 65% humidity:

- * Dry to Touch: 1 hour
- * Recoatable: 4 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOFONDO	1
ARMONY	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

2.5 Kg et 20Kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°294 .

Edition : June 2025 by Colorado 06/25 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001