



DESCRIPTION

Matt paint based on copolymer acrylic emulsions for standard work.

FIELD OF USE

COLO 7000 can be applied to interior and exterior masonry cladding; woodwork and plaster, it has a very good whiteness and a high covering power and good adhesion. It dries quickly, it is odorless and does not flour. It is washable and is very easy to apply.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors : Delivered in white, it can be tinted with our Tints 2000. Special tints are delivered for orders over 100 Kg.
- Spreading-rate : 5 to 6 m²/Kg depending on the porosity of the support. Compliant with ISO 23811 (2009).
- Density : 1,68 ± 0.05 at 25° C, Complies with NM ISO 2811-1 (2008).
- Dry extract (by weight) : 74% ± 2%.
- Viscosity : 460 ± 50 poises with a Brookfield viscometer at 25 ° C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

COLO 7000 can be applied with a roller or a brush without any risk of rework or seaming. Application limit: Do not apply on condensing or frozen substrates at temperatures below 5 ° C, and above 35 ° C, nor at relative humidity above 80%.

APPLICATION DETAILS OF USAGE

- Dilution:
- * 1st layer 15 to 20% water.
 - * 2nd layer 10 to 15% water.

DRYING TIME

At 20 ° C and 60% humidity:
 *Dust free: 15 min
 * Dry: 30 min
 Recoatable after 3 hours.

RECOMMENDED SYSTEM

■ EXTERIOR (*)

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM or Colofix	1
COLO 7000	2

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or Colofix	1
COLENDUIT Extra B505 or SP88	2
COLOFIX	1
COLO 7000	2

(*) System recommended to protect the substrate from carbonation thanks to its resistance to CO₂ diffusion.

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 kg, 30 Kg , 45 Kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 172-1.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001