



## DESCRIPTION

Two-component polyester putty, reinforced with glass fibers, for automotive repairs that require high filling power.

## FIELD OF USE

Colofibre is applicable to: Metal, Wood.

## CHEMICAL BASIS

Unsaturated polyester putty.

## GENERAL CHARACTERISTICS

- \* Very good filling power.
- \* Easy sanding.

## PHYSICAL PROPERTIES

- Relative density :  $1.60 \pm 0.05$  at  $25^{\circ}\text{C}$
- Dry extract weight :  $72 (\%) \pm 2$ .
- Color: Light gray, Smooth and matt appearance.
- Spreading-rate : depending on the condition of the substrate and the thickness

## APPLICATION DETAILS FOR USAGE

- Ready to use. Use D33 or D55 for cleaning. Catalyst: Tube of benzoyl peroxide mix at 3%. Service life in mixture with catalyst is 2 to 5 min.

## PACKAGING

0,5 Kg, 1Kg.

## DRYING TIME



Pot Life: 2 min to 5 min



Drying time at  $20^{\circ}\text{C}$  20 - 30min.

## CONDITIONS AND METHODS OF APPLICATION

- Ready to use.



Application material: Body knives



Drying time at  $20^{\circ}\text{C}$ : 20 to 30min



Sanding: Dry sand only

## STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N° 200.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001