



## DESCRIPTION

White undercoat essential before the application of finishing paints in waterborne. Allows to standardize the support in order to obtain a beautiful finish.  
Inside and outside.

## FIELD OF USE

Undercoat essential before the application of paints in waterborne essential especially on raw supports before painting of finishing products.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Color : White.
- Spreading-rate : 8 to 10 m<sup>2</sup>/L depending on the substrate, conforms to ISO 23811 (2009).
- Density : 1,35 +/- 0,05 Kg/L at 25°C, Complies with NM ISO 2811-1 (2008).
- Dry extract : 55 % in weight +/- 2%, Compliant with ISO3233-3 (2015).
- Viscosity : 100 +/- 5 KU at 25°C, Complies with ASTM D561 (1997).

## SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Application limit: Do not apply on condensing or frozen support, at temperature below 5 ° C nor at relative humidity above 65%.

## APPLICATION DETAILS OF USAGE

Application tool: anti-drip roller. Application conditions in accordance with standard NFP 74-201 (DTU 59.1).

The preparation of the base (new or old, covered or not) must be done according to standard NF P 74-201

(DTU 59.1) Prior recognition is necessary to determine the nature of the preparations and the possible impression.

## DILUTION & ADVICE

1st coat diluted with 10% water if necessary. Avoid wasting paint, estimate how much paint you need. Close any unfinished jars so that the paint can be reused.

Reusing paint is a good way to reduce the environmental impact of products over their entire life cycle.

Estimate the quantity needed before purchase in order to optimize cost and waste: 10L +/- 100 m<sup>2</sup>. For information on disposal methods, contact the local authorities.

## DRYING TIME

Drying at 20 ° C and 65% relative humidity:

- \* Dry to touch: 30 minutes.
- \* Recoatable: 4 hours.

## RECOMMENDED SYSTEM (contact us)

### ■ INTERIOR EXTERIOR :

SYSTEM	NUMBER OF COATS
COLOFIX	1
FINISHING PAINT	2

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

3 L, 10 L.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N ° 193.

## MINIMUM ORDER QUANTITY

B'VSeWUa` fSUfagdeS'W VbSof\_ Wfž

7V[f[a` , February \$ \$ 6 Tk 5a'adSva 02!\$6/65\*\$9fž

@24, FZWbgbdaeWxFZ[eFVfZ` [US^VSfSeZWW[efaf bdaHWW` Xad\_ Sf[a` a` fZWbcbWf[WaXagdbdVgUfZFW[` Xad\_ Sf[a` Ua` fS[ WfZVW[ [eTSeW a` agdUgdWfW ]` ai WYVWaXfVfeUsd[ W agf i [fZ S Lb` efS fLb` Ua` XadaTWW[hfk SUadV[ Y fa fZWUa` V[f[a` eaXgeW` SUad/S Ua` [fZ efS Vsd/ead6FG [` XadW ]` ai Wm1 FZW[ Xad\_ Sf[a` US` af dW SfMS` SbbcbabqSfWWWUfbf[` S` VfZWefSfWaXfZWg` Vefaf TWbS[ fWfž

FZ[eVWbUbfhWVfZ` [US^eZWW[US` UMeS` VdW/SfMS` k eZVWdMS` Y fa fZWes\_ WbdaVgUfZFWStahWfVfZ` [US^VSfS VaW` af [` b` k SfMS` UaXfZWgSd` fWfž

5'aefWfVbaf fYfZfK SfWfgeVf: Wb bdaVfWfVfZWW[h[da` \_ WFTK` af V[ebae` Y aXi SefW` fZWbS[ eadZageVfZa` Vi SefWfBfVfSfWfVfZdMfgd kagdW` bfk Sdfa S dWfUf` Y UfVfZfVfZdakgdg` geW` bdaVgUf b` VSeWUa` fSUfagd[ W Xad[ Sf[a` a` V[ebae` S` V Ua` Wf[a` ž