



DESCRIPTION

COLOFLASH ALUMINIUM is a topcoat based on peel-off metallic pigment giving the application a stretched film of chrome shine.

FIELD OF USE

For radiators, pipes ...

TECHNICAL CHARACTERISTICS

- Color: Aluminum gray
- Density : 0.94 +/- 0,05 at 25°C
- Spreading-rate : +/- 10m²/Kg
- Viscosity : 15 ± 2 seconds
- Dilution: Ready to use

APPLICATION PROPERTIES

Brush, roller, pneumatic gun.

DRYING TIME

Dry : 1 hour
Recoverable : 12 hours

STORAGE

The product can be stored for up to 2 years in its original closed packaging and in good storage conditions out of direct sunlight. It is nevertheless recommended to shake the product before use.

PACKAGING

85 g, 250g.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 609.

Edition : September 2021 by Colorado 09/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001