

COLOFONDO

Under-coat for decorative effect finishes based on an acrylic co-polymer



DESCRIPTION

Flat emulsion based under-coat (for Arabesk, Sicilia, Touareg Cachemire and Rimal) based on an acrylic co-polymer.

FIELD OF USE

COLOFONDO can be applied on masonry, wood and plaster substrates.

It has a high degree of whiteness and excellent covering power.

COLOFONDO dries quickly, has no smell, does not chalk and has good adhesion. It helps the application of decorative, special effect finishes like Florence, Arabesk, Sicilia, Touareg and Rimal.

TECHNICAL CHARACTERISTICS

- Aspect : Matt finish.
- Color : Delivered in white (for Arabesk and Rimal) or tinted (for Sicilia, Touareg Cachemire and Rimal). The following colours are available : Beige 455A, Orange 441B, Mauve 445 B, Salmon 430 C, Purple 429 B, Persimmon 444 B, Cream, Carlet, Grey, Red, Blue sky (H4933), Dark blue (H 4850), Green (pastel), Green, Brown, Pink.
- Spreading-rate : 9.6 to 11.2m²/L per coat depending upon the Surface porosity.
- Density : 1.6 Kg/L +/- 0.1 at 25°C.
- Viscosity : 130 +/- 5 KU's at 25°C with the Krebs Stormer.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before painting.

APPLICATION PROPERTIES

COLOFONDO can be applied with a brush or a roller without any risk of wet-edge problems. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USAGE

Dilution : tap water (10 to 15%)

DRYING TIME

Drying time: at 20°C and 60 % Relative Humidity :

* Touch Dry : 15 min.

* Through Dry : 60 min.

STORAGE

Twelve months in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

COLOFONDO : 1.6 liters (for 16 m²).

FONDO ATF : 4 Kg

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the safety data sheet N° 26.