



DESCRIPTION

Matt vinyl paint based on acrylic copolymer emulsion.

FIELD OF USE

Applies to interior and exterior substrates, such as cement plaster and plaster. It has good whiteness and coverage and is easy to apply.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors : Delivered in white, it can be tinted with our Colors 2000. Special colors are delivered for orders over 100 Kgs.
- Spreading-rate : About 5 m²/kg depending on the porosity of the support.
- Density : 1,68 +/- 0,05at 25°C.
- Viscosity : 560 +/- 50 poises at 25°C.

CONDITIONS AND METHODS OF APPLICATION

It is applied with a roller or possibly a brush. Generally, two coats are applied diluted according to the porosity of the support. Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 °C and / or relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: 5 to 15% with water.

DRYING TIME

- At 20 °C and 60% humidity:
- * Dust free: 15 min.
 - * Dry: 60 minutes.
 - * Interval between coats: minimum 3 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOFIX	1
COLOLATEX	2

■ EXTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
ENDUIT FACADE P20 or P10	2
COLOFIX	1
COLOLATEX	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

1kg, 5kg, 20kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 63.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001