



DESCRIPTION

Matt paint based on vinyl dispersion. AFNOR T36-005 class: Family I-class 7a2.

FIELD OF USE

COLOMAX can be applied to interior and exterior masonry, exterior, woodwork and plaster. It is odorless, has a very good whiteness and a good covering power.

TECHNICAL CHARACTERISTICS

- Aspect : Mat.
- Colors: Delivered in white, can be tinted with our Tints 2000.
- Spreading-rate : Approximately 5 m²/Kg depending on the porosity of the support.
- Density : 1,75 ± 0,05 Kg/L at 25° C.
- Viscosity : 250 ± 50 Brookfield viscometer at 25°C.

SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Apply with a roller or a brush. Limits of application: Do not apply on condensing or frozen supports by temperature lower than 5°C, nor by relative humidity higher than 70%.

APPLICATION DETAILS OF USAGE

- Dilution :
- * 1st coat: 10 to 15% water.
 - * 2nd coat: 5 to 10% water.

DRYING TIME

- At 20° C and 60% humidity:
- * Dry : 30 min.
 - * Recoverable : 4 h.

RECOMMENDED SYSTEM

■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1 or 2
COLOPRIM or COLOFIX	1
COLOMAX	2

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT Extra B505 or SP88	2
COLOMAX	2

STORAGE

The product can be stored for up to 2 years under good storage conditions away from the sun, however it is recommended to shake the product before use.

PACKAGING

1 kg, 5 kg, 10 kg, 30 kg, 45 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°124

Edition :Mai 2026 by Colorado 05/26 (DC28G).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001