



DESCRIPTION

Synthetic glossy lacquer based on modified alkyd resins for quick drying and universal use. Characterized by its hardness, elasticity and high resistance to weathering.

FIELD OF USE

Paint intended for the protection and embellishment of doors, furniture, vehicles, machines, etc ...

TECHNICAL CHARACTERISTICS

- Aspect : Bright.
- Colors : White, black, red, yellow, brown, blue, green, gray.
- Spreading-rate : 8,6 m²/kg/45 µm.
- Density : 1,00 à 1.15 + / - 0,05 à 25°C depending on the color.
- Dry extract (mass) : 62 +/- 2%.
- Dry extract (volume) : 44 +/- 2%.

SURFACE PREPARATION

Surfaces must be sound, clean and dry, suitably prepared and comply with standard DTU 59.1.

CONDITIONS AND METHODS OF APPLICATION

Material: Brush, roller or gun.

Application limit: Do not apply on condensing or frozen substrates at temperatures below 5 ° C, nor at relative humidity above 70%.

APPLICATION DETAILS FOR USAGE

Dilution: D66 brush (5 to 15%).
Pistol D77 (10 to 20%).

DRYING TIME

Drying at 20 ° C and 60% humidity:
*Dust free: 1.5 hours.
*Dry to touch: 6 hours.
* Recoatable: 24 hours.

STORAGE

The product can be stored for up to 2 years under good storage conditions, protected from direct sunlight, in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

1 kg, 250 g, 85 g.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N ° 279.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001