



DESCRIPTION

White printing essential before applying DECOSOL. It can be applied indoors on all types of floors.

FIELD OF USE

Printing essential before the application of DECOSOL. It reinforces the adhesion on all types of new or old floors in bob condition (raw, tiled, smoothed).

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Color : White.
- Dilution: up to 10% depending on the support.
- Spreading-rate : 8 to 10 m²/L depending on the medium.
- Density : 1,35 +/- 0,05 at 25°C.
- Dry extract: 60% by weight + / - 2%.
- Viscosity : 136 +/- 5 KU at 25°C.

CONDITIONS AND METHODS OF APPLICATION

It is imperative that you clean your floor with a brush to remove all traces of grease, cleaning products, etc. Rinse with clean water and let dry. If you want a smooth floor: first make a self-leveling leveling compound, otherwise you will keep the original appearance of your support (reliefs, tile joints, etc.). Optionally apply COLOFER on the tile joints in order to obtain a smooth surface.

Apply 2 coats of primer with an anti-drip roller crossing the application.

Wait 8 hours, before applying DECOSOL.

Limit of application: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C nor at relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Application tool: anti-drip roller.

Application conditions compliant with standard NFP 74-201 (DTU 59.1).

The preparation of the base (new or old, covered or not) must be done in accordance with standard NF P 74-201 (DTU 59.1) Prior recognition is necessary to determine the nature of the preparations and the possible impression.

DILUTION

1st coat diluted with 10% water.

DRYING TIME

Drying at 20 ° C and 60% relative humidity:

* Dry to touch: 30 minutes.

* Between two coats: 4 hours.

* Recoatable by DECOSOL: 8 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COAT
FONDO DECOSOL	2
DECOSOL	2
VARNISH DECOSOL	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

750 ml.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°103-2.

Edition : November 2020 by Colorado 11/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001