



DESCRIPTION

Thick decorative coating based on vinyl resin and colored mineral grains.

FIELD OF USE

Very appreciated in the decoration of corridors, stairwells, entrances, waiting rooms etc.

TECHNICAL CHARACTERISTICS

- Aspect : Matte and rough.
- Colors: White, available in several shades (see color chart).
- Spreading-rate : 2 to 3 kg/m².
- Density : 1,45 +/- 0,05 at 25°C.
- Viscosity : 2000 +/- 200.
- Dry extract by weight : 80% +/-2%.

SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

APPLICATION PROPERTIES

For both new and old surfaces, the surface must be dry, sound and free of all traces of contaminants. Apply (without diluting) with a thin stainless steel float.

APPLICATION DETAILS OF USAGE

Dilution : Ready to use.

DRYING TIME

Drying at 20°C and 60% humidity:

- * Dust-free: 1h30min.
- * Dry : 12 hours.
- * Recoatable: 24 hours.

RECOMMENDED SYSTEM

SYSTEM	NUMBER OF COATS
COLOPRIM *	1
COLOFONDO	1
GRANITO	1

(*) Optional: On porous facades, a coat of Coloprime will be necessary before applying Colofondo.

STORAGE

The product can be stored for up to 1 year under good storage conditions, away from sunlight and frost, in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

25 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on Safety Data Sheet N° 37.

MINIMUM ORDER QUANTITY

600 kg.

Edition : August 2025 by Colorado 08/25 (DC28G).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001