



DESCRIPTION

HYDROVINYL is a matt paint based on acrylic copolymers in waterborne for careful work.

FIELD OF USE

HYDROVINYL can be applied to masonry, woodwork and plaster coating.
Has very good whiteness, easy application and good abrasion resistance.

TECHNICAL CHARACTERISTICS

- Aspect : Matt et Smooth.
- Color : Supplied in white, it can be tinted with our Tints 2000.
- Spreading-rate : 7 to 9 m²/Kg per layer depending on the porosity of the support. Compliant with ISO 23811 (2009).
- Density : 1,69 ± 0,05 at 25°C. Complies with NM ISO 2811-1 (2008).
- Dry extract (by weight) : 73 ± 2%, Compliant with ISO3233-3 (2015).
- Viscosity : 460 ± 50 poises at 25°C at Brookfield.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

HYDROVINYL can be applied by roller or brush without any risk of rework or seaming.
Application limit: Do not apply on condensing or frozen substrates.
Indoor work: Minimum temperature of 8 ° C and 35 ° C max, relative humidity less than 70%.
Outdoor work: Minimum temperature of 5 ° C and 35 ° C max, relative humidity less than 80%.

APPLICATION DETAILS OF USAGE

- Dilution:
- * 1st layer 10 to 15% water.
 - * 2nd layer 5% water.

DRYING TIME

- At 20 ° C and 60% humidity:
- * Dust free: 15 min.
 - * Dry: 30 min.
 - * Recoatable after 3 hours.

RECOMMENDED SYSTEM (contact us)

■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM , COLOFIX	1
HYDROVINYL	2

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX or FORMORAL (*)	1
COLENDUIT Extra B505 or SP88	2
COLOFIX (Optionnel)	1
HYDROVINYL	2

(*) Depending on the support.

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

30 kg, 45 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 196.

Edition : September 2021 by Colorado 09/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001