



DESCRIPTION

One-component acrylic road paint, based water for marking roads, parking lots, sidewalks...
On asphalt, macadam and concrete. O'Route is suitable for airport marking.

FIELD OF USE

O'ROUTE Designed for ground marking, this paint will ensure clear and visible signage in compliance with the road safety. By adding glass microbeads, our paint can become retro-reflective and non-slip for optimal safety and visibility

TECHNICAL CHARACTERISTICS

- Gloss level : Mat
- Colour : White , Red , Yellow
- Viscosity : 85+/-5KU at 25°C.
- Density :
 - Red : 1,70 +/- 0,05 at 25°C.
 - Yellow : 1.65+/-0.05 at 25°C.
 - White : 1.66 +/-0.05 at 25°C.
- Volume-solids : 57 +/- 5%.

APPLICATION DETAILS OF USAGE

Application by dusting using a dusting machine conventional marking. Roller application possible.
Product ready to use, dilution not recommended. It is recommended to rehomogenize the product before use.

Do not apply at a temperature below 10°C, nor with humidity greater than 70%. Please apply at temperatures above 3°C at dew point

SURFACE PREPARATION :

Apply the paint to a dry, dust-free background, degreased, and, if necessary, prepare the surface (sanding, shot blasting, or sandblasting); If you want to cover a marking, check adhesion and compatibility of the paint. In ideally remove the markings to be covered (shot blasting, planing). On hydrocarbon coating (bitumen, tar, asphalt): Paint to be applied at a minimum one month after its completion (complete evacuation of sweating oils because they are harmful to good adhesion). On concrete coating: Do shot blasting to make the concrete surface more adherent.

DRYING TIME

- *Through-dry : 10 min.
- *-Dry to handle : 1h at 23°C

STORAGE

The product can be stored for up to 2 years under good storage conditions out of direct sunlight in its original packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

30 Kg .

HEALTH AND SECURITY

Water-based product, ready to use for professional use. Do not dilute the paint and never add solvent
Soiled packaging and cleaning products are to be treat according to current regulations.
Consult the Safety Data Sheet N°322.

MINIMUM ORDER QUANTITY

600 kg.

Edition : August 2025 by Colorado 08/25 (DC28G).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001

www.colorado.ma