



DESCRIPTION

PLIOSTAR is a self-cleaning refurbishment paint based on PLIOLITE resins. Complies with French Standard NF EN 1062-1.

FIELD OF USE

PLIOSTAR is used for all facade work and has excellent weather resistance. PLIOSTAR can be applied on cement, mortar, concrete, brick, cement plaster.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors: White, other colors on request.
- Spreading-rate : 5 to 6 m²/Kg.
- Densité : 1,57 ± 0,05 in white, at 25°C.
- Dry extract (by weight) : 73 ± 2%.
- Viscosity : 105 ± 5 KU .

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Application Equipment: Brush, roller or AIRLESS gun.
Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C, or at relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: White Spirit (D66)
*1st layer: 5 to 10%.
*2nd layer: 0 to 5%.

DRYING TIME

Séchage à 20°C et à 60% d'hygrométrie :

* Hors poussière : 15 min.

*Sec : 1 à 2 heures.

* Recouvrable : 24 heures.

RECOMMENDED SYSTEM

■ EXTERIEUR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10 (*)	1
PLIOSTAR diluted at 10%	1
PLIOSTAR	2

(*) On porous and chalky surfaces, apply a coat of Imprex Varnish before applying the facade plasters.

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 kg, 20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N ° 39.

Edition : October 2021 by Colorado 10/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001