



## RIMAL

Water-based decorative coating  
INTERIOR



67E5D;BF;A@

RIMAL is a water-based decorative effect finish with a metallic sand finish.

### FIELD OF USE

It is designed for interior decoration, giving a colored, pearlescent effect on walls.  
It is especially suitable for big surfaces like halls, dining rooms and flats.

### TECHNICAL CHARACTERISTICS

- Aspect : Colored Pearlescent metallic effect. Contains grains of sand
- Colors : See our catalogue.
- Spreading-rate : About 7.5 m<sup>2</sup>/Kg (9 m<sup>2</sup>/L +/- 1) in one single coat applied by brush or sponge.
- Density : 1.06 to 1.30 Kg/L +/- 0.05 depending upon the color at 25° C.
- Viscosity : 120 KU's +/- 5 at 25° C (Kreb Stormer).

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

Using a brush, apply over COLOFONDO an even coat over the surface.

Using a roller, apply over ACRYMAT an even coat over the surface.

Using the special ATF spatula, brush or sponge, apply RIMAL ALUMINIUM in all directions over the surface. To reduce the risk of lapping problems, work in areas of 1 to 2 m<sup>2</sup> in order to obtain the desired effect.

Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application (can be diluted with upto 5% of water)

Edition : June 2014 by Colorado (DC 28 D).  
This version replaces all previous editions.

### DRYING TIME

Prepare the surface with one or two coats of Colofondo (preferably tinted) or ACRYMAT and leave to dry for 12 hours :

Drying time at 20°C and 60% relative humidity :

- \* Touch dry : 3 to 4 hours.
- \* Dry : 24 hours.
- \* Washable : 20 days.

### RECOMMENDED SYSTEM

#### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT Extra B505 or SP88	2
COLOVINYL 600	1
COLOFONDO	1
RIMAL	1

### STORAGE

One year in the closed plastic container, as delivered.  
Store inside in conditions avoiding extremes of hot and cold temperatures. Keep away from heat / Sparks/ naked flames/ hot surfaces. Do not smoke.

### PACKAGING

- \* RIMAL : 2 liters
- \* FONDO : 4 Kg ou COLOFONDO : 1,6 Liters.
- \* ACRYMAT : 4 Kg

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the safety data sheet N° 30.