



& OEVJU QPVESF È CBTF EF DPQPMZNÒSFT WJOZ  
\*/5²3\* & 63



DESCRIPTION

SÉCHAGE

& OEVJU EF MJTTBHF QFSNFUUBOU E PCUFOJS VO BTF QDFDU MJTTT FU  
VOJGPSNF 1SPUÒHF DPOUSF M BMDBMJOJUÏ ÈNTF D'PQIFSUBQSÒT I  
DJNFOUT

DOMAINE D'UTILISATION

STOCKAGE

4\* - & / % 6 \* 5 7 FTU DPOÏV QPVS MFT USBWBVY JOUÏSJFVST  
& OEVJU EF MJTTBHF QFSNFUUBOU E PCUFOJS VO BTQFDU MJTTT FU  
VOJGPSNF

CARACTÉRISTIQUES TECHNIQUES

EMBALLAGE

- "TQF DU .BU
- 3FOEFNFOU & È EW T BHF  
3BUJTT È HF N L H
- & YUSBJU TFD

LH LH

SANTE ET SECURITE

D

PRÉPARATION DE SURFACE

- FT USBWBVY EPJWFOU TF GBSF DPOGPSNÏNFOU È MB OPSNF  
' % 56 FU TF SPOU SÏBMJTÏT BWFD MF QMVT HSBOE TPJO

CONDITIONS ET MÉTHODES D'APPLICATION

.BUÏSJFM SFDPNNBOEÏ \$PVUFBV È FOEVJSF  
-JNJUF E BQQMJDBUJPO /F QBT BQQMJRVFS TVS TVQQPSUT  
DPOEFOTBOUT PV HFMÏT QBS UFNQÏSBUVSF JOGÏSJFVSF È i \$  
OJ QBS IVNJEJUÏ SFMBUJWF TVQÏSJFVSF È

DÉTAILS DE LA MISE EN OEUVRE

\$FU & OEVJU TF QSÏQBSF QBS TJNQMF BEEJUJPO E FBV  
- FOEVJTBHF OÏDFTTJ È F VOF EJM VUJPO EF  
- F SBUJTTBHF OÏDFTT È F VOF EJM VUJPO EF

& EUJPO +VJMMFU % \$BS \$P

/ # -B QSÏTFOUF GJDIF UFDIOJRVF B QPVS C VLS È EJM QGPSNF S F O S F M F O F N S P O U S T J R U J T Z F G O H P V S F O U  
BDUVFMMFT E FTTBJT F G G F T P W A D I T B W E R F O U J D P O U T I U B O G P O D U J P O E F T D P O E J U J P O T E V U J M J T B U J  
5P V U F G P J T M F T S F O T F J H O F N F O U T O F Q F V W F O U T V Q Q M Ï F S È V O E F T D S J Q U J G B Q Q S P Q S J Ï F U È M  
-B QSÏTFOUF GJDIF UFDIOJRVF EFTDSJQUJWF BOOVMF FU SFNQMBDF UPVUF GJDIF SFMBUJWF BY  
HBSBO#UJFO SFGFSNFS MF QPU BQSÒT VTBHF \$POUSJCVF[ È QSÏTFSWFS M FOWJSPOOFNFOU FO  
SBQQPSUFS WPUSF QPU WJEF EBOT VOF EÏDIFUUSJF 1PVS WPUSF QSPEVJU JOVUJMTÏ W F V J M  
E ÏM J N J O B U J P O F U E F D P M M F D U F

\$0-03"%0 FTU DFSUJGJÏF \*40 \*40 FU \*40

XXX DPMPSBEP NB