



## DESCRIPTION

Powder coating based on vinyl copolymers. Smoothing filler for a smooth and uniform appearance. Protects against the alkalinity of cement substrates.

## FIELD OF USE

SILENDUIT V805 is designed for interior work. Smoothing coating to obtain a smooth and uniform appearance.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Spreading-rate : \* Coating: 2 to 3 m<sup>2</sup>/kg.  
\* Raking : 3 to 4 m<sup>2</sup>/kg.
- Dry extract : 100%.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Recommended material: Coating knife.  
Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C, or at relative humidity above 70%.

## APPLICATION DETAILS OF USAGE

This Plaster is prepared by simply adding water:  
\* Coating: requires a 20 to 30% dilution.  
\* Raking: requires a 30 to 40% dilution.

## DRYING TIME

- \* 1st coat: 1 hour.
- \* 2nd coat: after 24 hours.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

5kg, 25 kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 45.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001