



STELLA

Water-based decorative effect finish
INTERIOR

DESCRIPTION

STELLA is a water-based acrylic copolymer decorative effect finish.

FIELD OF USE

It is designed for interior decoration, giving a colored, pearlescent effect on walls with a scintillating special effect.
It is especially suitable for decorating large surfaces like halls, dining rooms and flats.

TECHNICAL CHARACTERISTICS

- Aspect : Colored, slightly Metallic with diamond like silver particles.
- Color : See our catalogue.
- Spreading-rate : About 4 m²/L (in 2 coats).
- Density : 1.15 Kg/L +/- 0.05 for argent base at 25° C.
- Viscosity : 108 KU's +/- 10 at 25° C (Kreb Stormer).

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

The work must be in accordance with the NF DTU59.1 and will be made with the utmost care.

APPLICATION PROPERTIES

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering.

Using a roller, apply an even coat of Colofondo (Tinted) over the surface. Let the Colofondo dry for 12 hours.

Using the special short pile roller, apply Stella (diluted with 20% of water) in all directions over the surface. To reduce the risk of lapping problems, work in areas of 1 to 2 m².

Leave the product to dry, before applying a second diluted coat (and if necessary a third coat) using the short pile roller. Using a blade or rendering tool, spread out the Stella in order to obtain the special effect.

Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Mix well before use.

Depending upon the application method used, this product can be diluted with upto 20% of tap water

DRYING TIME

Drying time at 20°C and 60% relative humidity:

- *Touch dry : 1 to 2 hour.s
- * Dry : 24 hours.
- *Washable : 20 days (with one coat of Coloprime).
- * Recouvrable : 6 Zogdż

RECOMMENDED SYSTEM

- INTERIOR (Consult us):

SYSTEM	NUMBRE OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505 ou SP88	2
COLOFONDO	1
STELLA	2
COLOPRIM (For wash resistance)	1

STORAGE

T in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

- *STELLA: 2,5 Litres.
- *COLOFONDO : 1.6 litres.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

Fore more details, consult the safety data sheet N° 98.

Edition : August 2016 by Colorado (08/16).
This version replaces all previous editions.