



DESCRIPTION

Varnish based on cellulose resins and modified synthetic resins.

FIELD OF USE

SURFACEUR S6 is specially designed to clog pores. Protects wood against humidity and light. It is a very viscous pore mouth with a very good filling. The pore sealer does not alter the color of the wood and thus contributes to giving a good finish to varnishes.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors: Yellowish with greenish reflection.
- Rendement : 14 to 16 m² / L (depending on the porosity and nature of the wood).
- Density : 0,95 +/- 0,05 at 25°C.
- Viscosity : 45 +/- 5 mn CF6 at 25°C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Can be applied directly to stained or unstained wood.
Recommended equipment: Brush, Spray gun.
Application limit: Do not apply on substrates condensing or frozen at temperature below 7 °C, nor at relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Thinner: About 30% with Cellulose Thinner D33.

DRYING TIME

- Drying at 20 ° C and 60% humidity:
- * Dust free: 10 to 15 minutes.
 - * Dry: 30 to 40min.
 - * Recoatable: After 1 hour.

STORAGE

The product can be stored for up to 1 year in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

750 ML, 5L.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N °274.

Edition : September 2021 by Colorado 09/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001