



DESCRIPTION

Special high resistance varnish for floors to protect your DECOSOL decorative effect. One-component varnish, PU, in waterborne, washable.

FIELD OF USE

Apply to DECOSOL in order to increase its resistance. As a general rule, Décosol varnish is compatible with all decorative effects in waterborne. Improves resistance, abrasion and leaching.

TECHNICAL CHARACTERISTICS

- Aspect : Whitish liquid product before transparent after drying.
- Color: Transparent.
- Shine: +/- 15% at 60°.
- Spreading-rate of the mixture : +/- 10 m²/L.
- Density : 1,08 +/- 0,05 at 20°C.
- Viscosity : 120 +/- 0,05 KU at 25°C.

CONDITIONS AND METHODS OF APPLICATION

For easy application and optimum performance, the surface must be clean, sound and dry.
 Let DECOSOL dry for 8 hours.
 Using a lacquer roller and always in the same direction, apply a 1st layer of protector diluted with 10% water. Important: to avoid repeat marks, the application must be fast and avoid overlaps. Let dry 4 hours before applying the second pure coat in the same way, but perpendicular to the 1st coat.
 Wait 24 hours before walking on your floor. For intensive use, wait a week.
 VERNIS DECOSOL also protects traditional concrete floors, you will need to wash and rinse them beforehand. Apply three coats of protector, diluting the 1st coat with 10% water.

- * Do not apply on substrates condensing or frozen at temperatures below 5 ° C or at relative humidity above 70%.
- * Recommended material: Brush or lacquer roller.

APPLICATION DETAILS OF USAGE

Product ready to use.
 Dilute the 1st coat, if necessary, between 5 to 10% water.
 Application tool: brush, lacquer roller (foam excluded).
 Application conditions in accordance with the NFP standard 74-201 (DTU 59.1).

DRYING TIME

- At 20 ° C and 60% humidity:
- * Dust dry: 30 min.
- * Dry to the touch: +/- 1 hour.
- * Recoatable: 4 hours minimum.

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

750 ml.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°146.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001